



Description

- FM / VdS approved
- The telescope pipe is an adjustable-length drop nipple to be used in fixed fire extinguishing systems. It allows the exact adjustment of sprinkler heads (inclusive escutcheons) in the centre of the tile. The adjustment can be made after the complete installation of the pipe system.
- The adjustment of the length is done by screwing the inside pipe in or out. This is possible when the system is under pressure. The O-ring seals the gap between the two pipes.
- Working pressure: PN25 (25 bars)
- Working temperature: -20°C to + 110 °C
- Finish coat : black painting



Telescope pipe

Reference	Description	Length (mm)		Adjustment (mm)	Connections		Weight (kg)
		mini	maxi		Inlet	Outlet	
	Telescope pipe				1" M	1/2" F	
CHVS0,1MF100-160	Telescope pipe	100	160	60	1" M	1/2" F	0.4
CHVS0,2MF140-240	Telescope pipe	140	240	100	1" M	1/2" F	0.6
CHVS0,3MF220-320	Telescope pipe	220	320	100	1" M	1/2" F	0.7
CHVS0,1MF3/4140-200	Telescope pipe	140	200	60	1" M	3/4" F	0.4
CHVS0,23/4MF180-300	Telescope pipe	180	300	120	1" M	3/4" F	0.65