

## VENF.EX6276 - Flexible Sprinkler Hose with Fittings

## Flexible Sprinkler Hose with Fittings

**KOFULSO CO LTD**

23 Bodeum-ro Seo-gu  
Incheon, 22665 Republic of Korea

EX6276

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
EFB224 braided	175	225	1x1/2	2.0 (610)	1	4	18	Limited
EFB228 braided	175	225	1x1/2	2.3 (710)	2	4	23	Limited
EFB231 braided	175	225	1x1/2	2.6 (785)	2	4	27	Limited
EFB236 braided	175	225	1x1/2	3.0 (915)	2	4	31	Limited
EFB240 braided	175	225	1x1/2	3.3 (1015)	3	4	39	Limited
EFB248 braided	175	225	1x1/2	4.0 (1220)	3	4	48	Limited
EFB260 braided	175	225	1x1/2	5.0 (1525)	4	4	60	Limited
EFB267 braided	175	225	1x1/2	5.6 (1700)	4	4	68	Limited
EFB272 braided	175	225	1x1/2	6.0 (1830)	4	4	71	Limited
EFB324 braided	175	225	1x3/4	2.0 (610)	1	4	18	Limited
EFB328 braided	175	225	1x3/4	2.3 (710)	2	4	28	Limited
EFB331 braided	175	225	1x3/4	2.6 (785)	2	4	30	Limited
EFB336 braided	175	225	1x3/4	3.0 (915)	2	4	34	Limited
EFB340 braided	175	225	1x3/4	3.3 (1015)	3	4	40	Limited

EFB348 braided	175	225	1x3/4	4.0 (1220)	3	4	51	Limited
EFB360 braided	175	225	1x3/4	5.0 (1525)	4	4	65	Limited
EFB367 braided	175	225	1x3/4	5.6 (1700)	4	4	70	Limited
EFB372 braided	175	225	1x3/4	6.0 (1830)	4	4	72	Limited
EFU224 unbraided	175	225	1x1/2	2.0 (610)	2	4	18	Limited
EFU228 unbraided	175	225	1x1/2	2.3 (710)	2	4	23	Limited
EFU231 unbraided	175	225	1x1/2	2.6 (785)	2	4	27	Limited
EFU236 unbraided	175	225	1x1/2	3.0 (915)	2	4	31	Limited
EFU240 unbraided	175	225	1x1/2	3.3 (1015)	3	4	39	Limited
EFU248 unbraided	175	225	1x1/2	4.0 (1220)	3	4	48	Limited
EFU260 unbraided	175	225	1x1/2	5.0 (1525)	4	4	60	Limited
EFU267 unbraided	175	225	1x1/2	5.6 (1700)	4	4	68	Limited
EFU272 unbraided	175	225	1x1/2	6.0 (1830)	4	4	71	Limited
EFU324 unbraided	175	225	1x3/4	2.0 (610)	2	4	18	Limited
EFU328 unbraided	175	225	1x3/4	2.3 (710)	2	4	28	Limited
EFU331 unbraided	175	225	1x3/4	2.6 (785)	2	4	30	Limited
EFU336 unbraided	175	225	1x3/4	3.0 (915)	2	4	34	Limited
EFU340 unbraided	175	225	1x3/4	3.3 (1015)	3	4	40	Limited
EFU348 unbraided	175	225	1x3/4	4.0 (1220)	3	4	51	Limited
EFU360 unbraided	175	225	1x3/4	5.0 (1525)	4	4	65	Limited
EFU367 unbraided	175	225	1x3/4	5.6 (1700)	4	4	70	Limited

EFU372 unbraided	175	225	1x3/4	6.0 (1830)	4	4	72	Limited
EFB 224 UP Braided	300	300	1x1/2	2.0 (610)	2	2.5	10	Limited
EFB 231 UP Braided	300	300	1x1/2	2.6 (792)	4	2.5	16	Limited
EFB 236 UP Braided	300	300	1x1/2	3.0 (914)	5	2.5	22	Limited
EFB 240 UP Braided	300	300	1x1/2	3.2 (975)	6	2.5	26	Limited
EFB 248 UP Braided	300	300	1x1/2	4.0 (1219)	8	2.5	34	Limited
EFB 260 UP Braided	300	300	1x1/2	5.0 (1524)	10	2.5	40	Limited
EFB 267 UP Braided	300	300	1x1/2	5.6 (1706)	11	2.5	45	Limited
EFB 272 UP Braided	300	300	1x1/2	6.0 (1828)	12	2.5	46	Limited
EFB 324 UP Braided	300	300	1x3/4	2.0 (610)	2	2.5	10	Limited
EFB 331 UP Braided	300	300	1x3/4	2.6 (792)	4	2.5	16	Limited
EFB 336 UP Braided	300	300	1x3/4	3.0 (914)	5	2.5	22	Limited
EFB 340 UP Braided	300	300	1x3/4	3.2 (975)	6	2.5	26	Limited
EFB 348 UP Braided	300	300	1x3/4	4.0 (1219)	8	2.5	34	Limited
EFB 360 UP Braided	300	300	1x3/4	5.0 (1524)	10	2.5	40	Limited
EFB 367 UP Braided	300	300	1x3/4	5.6 (1706)	11	2.5	45	Limited
EFB 372 UP Braided	300	300	1x3/4	6.0 (1828)	12	2.5	46	Limited

The braided type flexible sprinkler hose with fittings, Model EFB are intended to be installed with the Model TBS brackets in accordance with the manufacturer's installation instructions dated November 2017.

The unbraided type flexible sprinkler hose with fittings, Model EFU are intended to be installed with the Model OTBSR-PA brackets in accordance with the manufacturer's installation instructions dated February 2020.

The braided type flexible sprinkler hose with fittings, Model EFB ### UP are intended to be installed with the Model OGSR-02 bracket in accordance with the manufacturer's installation instructions dated January 2022.

Trademark and/or Tradename: **EASYFLEX**

Last Updated on 2022-02-08

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2022 UL LLC."