

# Model KFSP-BWDC

## Product Specification

Model No	NPT		K-Factor	Minimum Bend Radius		Number of Bends	Rated Working Pressure		Hose Assembly Length		Equivalent Length of 1 in. Schedule 40 Pipe	
	in	(mm)		in	(mm)		psi	(kPa)	in	(mm)	ft	(m)
KFSP-BWDC-01A	1/2	(15)	5.6	8	(203)	1	175	(1205)	30	(760)	18.8	(5.7)
KFSP-BWDC-02A	1/2	(15)	5.6	8	(203)	2	175	(1205)	47	(1190)	29.2	(8.9)
KFSP-BWDC-03A	1/2	(15)	5.6	8	(203)	3	175	(1205)	67	(1700)	38.3	(11.7)

1 in. nominal dia. flexible metal hose for providing a connection to automatic sprinklers in ducts. Approval is limited for use in square flange metal ducts.

### Description

KF: Kofulso (Manufacturer's initials)

B: Braided hose

SP: Sprinkler

C: Circular

D: Duct

W: Welded

Flexible Hose Lengths:

01 = 30 in. (760 mm)

02 = 47 in. (1190 mm)

03 = 67 in. (1700 mm)

A: 1/2 in. NPT

## Details

**Certification Type :** FM Approved

**Listing Country :** South Korea

**Approval Standard :** FM 1637 - Flexible Sprinkler Hose With

Threaded End Fittings

**Use :** Ducts

**Category :** Flexible Sprinkler Hose with Fittings, Ducts

## Company

**Kofulso Co Ltd**

23 Bodeum-ro, Seo-gu, Incheon, 404-330 South Korea

South Korea

<http://kofulso.co.kr>